

ULTRA CLEAN
LUBRICATED AIR COMPRESSOR

ULTRA CLEAN

LUBRICATED AIR COMPRESSOR



- **COMPRESSOR DESIGN OFFERS THE QUIETEST COMPRESSORS IN THE INDUSTRY**
- **THE AIR IS DRIED BEFORE THE TANK TO PREVENT BACTERIA BUILD UP IN THE TANK**
- **ALL MODELS HAVE DESICCANT AIR DRYING SYSTEMS**
- **ENERGY EFFICIENT MOTOR REDUCES THE NEED FOR COSTLY BOOST TRANSFORMERS**
- **COMPRESSORS ARE AVAILABLE IN SINGLE, DUAL OR TRIPLE HEAD CONFIGURATIONS**
- **VIBRATION FREE COPELAND HEADS PROVIDE SMOOTH RUNNING COMPRESSORS**
- **AIR INTAKE FILTERS TRAP DIRT, DUST AND AIR BORN POLLUTANTS**
- **ENERGY EFFICIENT THERMALLY PROTECTED MOTORS**
- **MOISTURE INDICATORS STANDARD ON ALL MODELS**

***TW* TECH WEST INC.**

Manufacturers of Dental Vacuum
and Air Systems

2625 N. Argyle Ave. • Fresno, CA 93727
(559) 291-1650 • (800) 428-7139 • FAX (559) 348-9677

LUBRICATED AIR COMPRESSOR

Tech West Ultra Clean Lubricated Air Compressors are designed to meet your needs with our high performance drying system. We guarantee the clean, dry, oil free air you expect. The design of the lubricated compressor offers vibration free running. They are offered in a variety of configurations; singles, duels or triples to meet any need.

Tech West will provide full plumbing and electrical design upon request.

FEATURES

- Large cooling fan on each compressor head.
- Oil drain tubes on all lubricated compressor heads.
- Drying system has a built in purge cycle.
- Built in handles on all compressors.
- All compressor tanks are epoxy coated on the inside to meet ASME standards.
- Redesigned Air Dryer makes the unit more compact and reliable.
- One handle dryer shutdown.
- Moisture indicators on the outlet air line.

BENEFITS

- Provides cooling air to the heads prolonging compressor life.
- Easy maintenance of the compressor when changing the oil.
- Removes all condensation from the desiccant to insure clean dry air.
- To make lifting and installing the compressor easy.
- To prevent rust and corrosion damage to the tank.
- This allows the compressor to be installed under cabinets and in closets, saving space.
- Quick shutdown and ability to continue working until a service call can be made.
- Early indication of moisture in the air before any condensation occurs.

LUBRICATED AIR COMPRESSOR

MODEL NUMBER	MAX USERS	AIR DRYER	# OF HEADS	TOTAL H.P.	CFM	TANK GALLONS	VOLTAGE	TOTAL AMPS	BREAKER SIZE	DB(A)	EQUIP. WEIGHT	EQUIP. HEIGHT	EQUIP. WIDTH	EQUIP. DEPTH	SHIPPING WEIGHT	SHIPPING HEIGHT	SHIPPING WIDTH	SHIPPING DEPTH
ACL2S1	2	YES	1	1	4.7	10	115	18	20	63	200	30	26	18	230	37	35	30
ACL2S2	2	YES	1	1	4.7	10	230	6.4	20	63	200	30	26	18	230	37	35	30
ACL4D2	4	YES	2	2	9.4	20	230	12.8	20	65	310	33	36	22	360	43	42	31
ACL6T2	6	YES	3	3	14.1	30	230	19.2	30	68	450	35	41	24	500	43	42	31

Revised 1/05

ALL LUBRICATED COMPRESSORS CARRY A FULL TWO YEAR WARRANTY



Exceeds NFPA 99C Guidelines



2625 N. Argyle Ave. • Fresno, CA 93727
(559) 291-1650 • (800) 428-7139 • FAX (559) 348-9677

FDA
RECOGNIZED